

# PREMIER

Multi-Purpose, High Strength Aerosol Flooring Adhesive



## PRODUCT DESCRIPTION:

SURfast is a multi-purpose flooring adhesive designed specifically to bond vinyl plank and tiles, VCT and carpet tile to a variety of substrates. SURfast may also be used for other general purpose flooring adhesive applications. The canister and aerosol rapid delivery system provides labor savings and unbeatable performance.

- Quick drying with permanent tack
- Excellent plasticizer resistance
- Outstanding moisture resistance
- Tenacious bond strength
- LEED, SCAQMD, OTC Compliant
- Low Odor
- No VOC's
- Quick Dry Time
- Extended Open Times for Maximum Workability
- High Solids for Greater Coverage
- Easy Clean Up
- Water Based
- Non-Flammable
- Proprietary Antimicrobial Protection
- Available in both aerosol and canisters

## TYPICAL USES & APPLICATION:

- Above, on, and below grade concrete (max. moisture emission rate of 10 lbs./1000 sq ft/24 hours, or RH 85%, and a max. pH of 11.0)
- Underlayments
- Plywood (underlayment grade)
- Oriented Strand Board (OSB) [underlayment grade]
- Hardboard
- Existing non-cushion back resilient floors (must be well bonded, sound, smooth, and free of all waxes, finishes, strippers, and cleaners)
- Ceramic Tile, Terrazzo, and Marble (smooth or glazed surfaces must be abraded).

NOTE: While some Lauan underlayments are acceptable [Type 1 (Exterior) BB and CC, or OVL] there are a variety of qualities and species sold as Lauan. Some varieties present severe problems when used as underlayments. Frequent problems noted are discoloration, indentation, bond failure, and underlayment delamination.

APPLICATION: Repair all joints and cracks. Remove all coatings, oil, water, dust and any other contaminant that may affect bond strength. SHAKE WELL BEFORE USE. The installation site must be acclimated with HVAC in operation. Sub-floor preparation, moisture and alkalinity testing must comply with industry standards, and floor-covering manufacturer's guidelines. The floor and room temperature, as well as flooring materials and adhesive, must be maintained at 65° - 95° F, and the humidity below 85% for 48 hours prior to, during and after the testing and installation. Hold spray can or gun tip approximately 30 inches from surface to be covered. Apply evenly. Do not allow to concentrate or puddle in one area. FOR RE-POSITIONABILITY, apply lighter adhesive coating (150 -160 sq ft/lb), allow the adhesive to dry completely before placing carpet tiles. Clean up overspray with damp cloth immediately after application.

(PLEASE NOTE: Due to the many additives being used in or on concrete slabs, it is critical that a bond test be performed. Some treatments will repel any sealer or adhesive. If usage instructions are not completely followed, DO NOT USE THIS PRODUCT.)

For Strong Permanent Bonds apply at the rate of 100 to 125 sq ft/lb. Best results are achieved if flooring is installed while adhesive is still slightly damp. Roll installed flooring with a 100 lb weight roller to ensure good contact.

