

# STAND and DELIVER

WITH NEW SURFAST FLOORING ADHESIVES

**SURfast**  
FLOORING ADHESIVE



- BONDS CARPET TILES, VCT, LUXURY VINYL and other similar flooring
- EASY TO APPLY WHILE STANDING
- NO MESSY TROWLING
- SAVES TIME AND MONEY
- SELF-PRESSURIZED, SELF CONTAINED, no external power needed
- AVAILABLE IN 17 OZ. AEROSOL CANS, 30 LB CYLINDERS
- EXCELLENT WATER AND PH RESISTANCE
  - LEED Compliant
  - No VOC's
  - Quick Dry Time
  - Extended Open Times for Maximum Workability
  - High Solids for Greater Coverage
  - Easy Clean Up
  - Water Based
  - Non-Flammable
  - Proprietary Antimicrobial Protection



**CALL NORTHSTAR CHEMICALS, Inc. at 770-386-6961 for more information and to arrange a demo.**

[getglue@northstarchemicals.com](mailto:getglue@northstarchemicals.com), [www.northstarchemicals.com](http://www.northstarchemicals.com)

# SURfast

FLOORING ADHESIVE



## SURfast CT 250

Designed for releasable carpet tiles and cushion to floor installations. Quick drying with permanent tack and excellent plasticizer resistance. Available in 30 lb canisters.



## SURfast VCT 500

Quick drying adhesive designed for strong permanent bonds needed for VCT. Easy and fast to apply. Available in 30 lb canisters.



## SURfast LT 800

High performance adhesive designed for luxury vinyl tiles and other demanding applications. Available in 30 lb canisters.



## SURfast PREMIER

Multi-purpose aerosol adhesive designed for carpet tiles, VCT, luxury vinyl and other similar flooring. Available in 17 oz aerosol.



## SURfast Adhesive Cleaner

ACR Adhesive Cleaner / Remover is an environmentally safe, biodegradable cleaner. Available in 14 oz aerosol and 8 and 28 lb canisters.



*Gun, tips and hoses sold separately.*

**SUBSTRATES:** Can be used on properly prepared concrete, APA approved plywood, metal, terrazzo, and existing clean, well bonded and prepared vinyl flooring. Adhesive cannot be used over old existing adhesive or sub-floors that have been chemically cleaned. It must be applied to a clean surface free of dirt, dust, and unapproved curing or sealing compound. Can be used for MVER up to 5 pounds/1000 sq. ft./24 hours (ASTM F1869), pH max 9 (ASTM F-217C).

**INSTALLATION:** SHAKE WELL BEFORE USE. For canisters, attach gun and hose. Leave hooked up and pressurized until canister is empty, then transfer to a new canister to prevent gun and hose from drying out. The installation site must be acclimated with HVAC in operation. Sub-floor preparation, moisture and alkalinity testing must comply with industry standards, and floor-covering manufacturer's guidelines. The floor and room temperature, as well as flooring materials and adhesive, must be maintained at 65° - 95° F, and the humidity below 65% for 48 hours prior to, during and after the testing and installation. Hold spray can tip or gun approximately 30 inches from surface to be covered. Apply even coats. Do not allow it to concentrate or puddle in one area. Clean up overspray with damp cloth before adhesive dries.

FOR REPOSITIONABILITY, allow the adhesive to dry completely before placing carpet tiles. FOR STRONG, PERMANENT BONDS, best results are achieved if flooring is installed while adhesive is still slightly damp and if flooring is rolled with a 100 lb weight roller.

**CLEAN-UP:** Invert aerosol can and spray until nozzle is clear. For canister systems, loosen and remove cap nut at end of gun, remove tip and thoroughly clean both tip and end of gun with ACR REMOVER or water to remove all traces of adhesive, then reassemble to be ready for next job. For short periods, cap can also be placed over tip or tip immersed in water to prevent drying. DO NOT ALLOW adhesive to dry in tip. If tip becomes clogged with dry adhesive, soak in mineral spirits to remove or replace tip.

**SHELF LIFE:** 6 months from manufacturing date, in an unused container. PROTECT FROM FREEZING.

**CALL NORTHSTAR CHEMICALS, Inc. at 770-386-6961 for more information and to arrange a demo.**  
getglue@northstarchemicals.com, www.northstarchemicals.com